

## TRANSMISSION FLUID



# PENTOSIN FFL-4

## Fully Synthetic Double Clutch (DCT) Transmission Fluid

### DESCRIPTION

**Pentosin FFL-4** is the only approved First Fill and Service Fill transmission fluid for the new generation of BMW double clutch gear transmissions (DCT). Pentosin FFL-4 is founded on a fully synthetic base oil technology for safe operation at even the highest thermal load. FFL-4 features a special clutch friction performance which makes it mandatory to be applied solely to the double clutch gear box – do not mix with any other gear oils.

SIZE	PART NUMBER	GTIN-13
1 Liter	1080107	4008849173332
20 Liter	1080208	4008849173431

### PRODUCT ATTRIBUTES

Appearance	Amber & Clear
Density at 15°C	842 kg/m <sup>3</sup>
Density at 20°C	839 kg/m <sup>3</sup>
Kinematic Viscosity at 100°C	7 mm <sup>2</sup> /s
Kinematic Viscosity at 40°C	34.7 mm <sup>2</sup> /s
Kinematic Viscosity at 20°C	83.9 mm <sup>2</sup> /s
Viscosity Index	168
Dynamic Viscosity at -40°C	7400 mPa*s
Pour Point	-54°C/-65.2°F
Flash Point	220°C/428°F
pH Value	N/A

### OE REFERENCE NUMBERS/RECOMMENDATIONS

Make	Reference Number
BMW	83 22 0 440 214
BMW	83 22 2 147 477

Always consult the vehicle owner's manual to identify fluid specification requirements. MSDS available to professional installer upon request.

© 2012 CRP Industries Inc. Pentosin is a trade name of Deutsche-Pentosin Werke. All rights reserved.

**DISCLAIMER:** CRP Industries Inc. has made every effort to assure the accuracy of the information on this product data sheet. Neither CRP Industries Inc., nor its affiliates assume responsibility for any loss or damage due to any errors, omissions or manufacturing changes.

PENTOFFL4-011510



CONTITECH | REIN | PENTOSIN | AJUSA  
OE quality brands for import applications.